

LS Pro 9500 MID Non-Contact Length & Speed Measurement System

Intelligent, compact measurement system with highest accuracy in accordance with European Directive MID

The LaserSpeed® Pro gauge is the industry's leading non-contact length and speed gauge offering the highest accuracy and reliability. The LaserSpeed Pro 9500 MID series measurement system includes the Beta LaserMike DataPro 1000 MID display and is certified to meet the requirements of the European Measuring Instruments Directive (MID). This approval has been granted by the National Measurement Office (NMO) in 2018 under the control number UK/0126/0023-Revision 5.

The LaserSpeed Pro series gauge has no moving parts, uses 100% solid-state digital technology and is permanently calibrated resulting in significant time and money savings. An integrated and enhanced version of autocorrelation feature, along with an acousto-optical modulator, enables the LaserSpeed Pro 9500 series gauge to measure forward and reverse directions as well as down to zero speed (no motion). All LaserSpeed Pro series gauges deliver better than $\pm 0.03\%$ accuracy to meet the Class 1 status of the EU Directive ($\pm 0.125\%$).

The MID policy was enacted in April 2004 and covers a number of measuring instrument types including gas and electricity meters, petrol pumps and automatic weighing instruments. The primary aim of the Directive is to harmonize the essential requirements of legal metrological control across all member states of the EU prior to placing products on the market. Older systems, such as devices with no measurement traceability or ones that have been in long-term storage, will no longer be valid.

The LaserSpeed Pro 9500 MID system meets the latest EU requirements. It is an ideal replacement for error-prone, mechanical-type encoders (tachometers) that can lose contact on product surfaces due to slippage, vibration and debris build-up, and cause damage to material. Our global customer service and support organization offers installation support for LaserSpeed Pro 9500 MID systems and provides effective communication with the certifying authorities to simplify the transition process.



Benefits

- ▶ High accuracy and repeatability
- ▶ Direct replacement for tachometers
- ▶ No moving parts to wear out
- ▶ Permanently calibrated
- ▶ Low cost of ownership
- ▶ Measures forward and reverse directions and zero speed (no motion)
- ▶ Provides long-term data storage with traceability of measured values
- ▶ Non-contact length and speed measurement
 - No slippage
 - Not affected by material surface or color
 - Non-marking

Range of Applications

LaserSpeed Pro gauges are well suited for a range of applications including:

- ▶ Wire, cable and optical cable
- ▶ Paper and corrugated products
- ▶ Non-woven products
- ▶ Rubber tube and hose
- ▶ Plastic pipe and tube
- ▶ Plastic films and tapes
- ▶ Building materials
- ▶ And more...

Accessories

- ▶ **Guide Rollers/Height Stand**
Various guides and height stand options are available for standard applications.

- ▶ **Laser Safety Enclosure**
Protects operators from direct or indirect laser beam exposure. Meets the EU laser safety requirements.



LS Pro 9500-4XX MID	-403	-406
Standoff Distance	300 mm (12 in.)	600 mm (24 in.)
Speed Range	0 to ±2000 m/min (0..±6,560 ft/min)	0 to ±2000 m/min (0..±6,560 ft/min)
Measurement Depth of Field	35 mm (1.4 in.)	50 mm (2 in.)

LS Pro 9500-4 MID (Continuous Length/Speed Measurement)

Accuracy	±0.125% of reading (instrument accuracy better than ±0.03%)	Controller Power	120/240 @ 4 Amp (including Gauge)
Repeatability	±0.02%	Spot Size	3 x 5 mm
Measurement Rate	>100,000/s	Gauge Size	203 X 159 X 95.2 mm (8.0 X 6.3 X 3.75 in.)
Acceleration Rate	>500 m/s ²	Gauge Weight	3.4 kg (7.5 lbs)
Status via Serial I/O (Gauge)	- Laser at Temperature - Laser On - Shutter Open - Valid Measurements	Ambient Temperature	5 to 40°C (41 to 104°F) Cooling/heating is required for temperatures outside this range
Serial I/O (Controller) Data Available	- RS-232 ,Ethernet - Length, Length Report - USB Printer port	Relative Humidity	Non-condensing 65%
Serial Baud Rate	- 1200, 2400, 4800, 9600, 19.2K	Degree of Protection	IP67 (Gauge) IP54 (Controller)
Status via Serial I/O (Controller)	- Length - Date - Time	Units of Measure	m/min
		Product Warranty	2 years
		Diode Warranty	3 years

Specifications are subject to change without notice.

Inputs		
Input	Description	Details
1	End of Reel Report	Prints the Date, Time & Current Length to the USB printer port
2	Transmit Length	Outputs the Date, Time & Current Length over RS-232
3	Transmit Length Report	Outputs the Date, Time, Machine Number, Product Number & Current Length over RS-232
4	Transmit Stored Data	Transmit the stored flash memory data (last 90 days) over the EtherNet port
5	Length Reset	Resets the current length

Outputs				
Control Output Type	Length Measurement Mode			
	Relay 1	Relay 2	Relay 3	Relay 4
Relay Closure	Preset Length Reached	Preset Length Approach	Quality Factor Warning	Quality Factor Reject

This unit is a class 3B laser product and Complies with IEC/EN60825-1:2014. Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.



The following safety features required to comply with the Bureau of Radiological Health Class IIIB laser requirements are included:

- Key-operated power switch on optional controller
- Laser indicator light on supply and laser
- Delayed laser startup-laser indicator light on prior to laser radiation
- Laser beam blocking device
- Interlock capability for remote shut-off

NDC Technologies is represented in over 60 countries worldwide. www.laserspeed.eu

NDC Americas
Tel: +1 937 233 9935
Email: sales@betalasermike.com

NDC China
Tel: +86 21 6113 3617
Email: sales@betalasermike.com

NDC India
Tel: +91 9971232913
Email: sales@betalasermike.com

NDC Europe
Tel: +44 1621 852244
Germany only: 08001123194
Email: sales@betalasermike.com

NDC SE Asia
Tel: +65 91994120
Email: sales@betalasermike.com

In line with its policy of continuous improvement, NDC reserves the right to revise or replace its products or services without prior notice. The information contained in this document may not represent the latest specification and is for indicative purposes only.

Document #: C&T-BROC-SYST-LaserSpeed_MID-EN-2020SEPT09
Date of Issue: September 2020
© NDC Technologies 2020

Intelligence that transforms the world.